



TR INDUSTRIES
11022 Vulcan Street
South Gate, CA 90280
Phone 562-923-0838 • Fax 562-861-3475

TR-309

REGULAR COMPOUND

DESCRIPTION:

TR-309 is a medium coarse white paste compound developed specifically for light oxidation and sanding scratch removal on polyester gel-coats.

PRODUCT FEATURES:

- Fast cutting action for quick effective removal light sanding marks
- Good initial gloss achieved on finished parts when sanding for minor defect repair
- Remains moist while buffing with less spotting and drying
- Restores gloss to lightly oxidized & weathered finishes

PHYSICAL PROPERTIES:

SPECIFIC GRAVITY: 1.23 (10.25lbs./Gal)

VISCOSITY: soft paste . water/petroleum emulsion blend

COLOR: off-white

USES:

To provide good initial uniform gloss while removing sanding scratches (600g-800g), light oxidation and minor surface imperfections on all gel coated finishes.

APPLICATION:

Apply **TR-309** to gel-coated surface and spread evenly. Using a high speed electric variable speed buffer equipped with all wool twisted buffing pad set buffer speed to 2,400 RPM for best results. Work in a 2qx 2q overlapping surface area using medium pressure to keep surface moist to avoid drying out and burnishing. As polish begins to dry gradually reduce buffing pressure to achieve a smooth uniform gloss appearance.

NOTE:

For optimum results polish with **TR-308** Fine Finish II to achieve a high gloss mirror like swirl free finish after using **TR-309** regular compound.

TR-309 is available in Gallon 4x1 case, 5gal pail or 55gal drum. Recommended to store in a cool dry place to maintain one year shelf life stability.

The information contained herein is based on tests considered to be reliable and accurate. Because of the wide variance of associated materials and conditions, however no warranty is expressed or implied. Each user is encouraged to prepare a test part for their particular application.